

Code	Inside Diameter		Outside Diameter		Working Pressure		Burst Pressure		Nominal Weight		Bending Radius		Length Max	
														
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	mm	inch	m	ft
LPGH-8	13	1/2	24	0,95	25	375	100	1500	0,39	0,26	100	3,9	60	200
LPGH-12	19	3/4	32	1,26	25	375	100	1500	0,62	0,42	180	7,1	60	200
LPGH-16	25	1	38	1,50	25	375	100	1500	0,77	0,52	200	7,9	60	200
LPGH-20	32	1-1/4	46	1,81	25	375	100	1500	1,04	0,70	250	9,9	60	200
LPGH-24	38	1-1/2	54	2,13	25	375	100	1500	1,35	0,91	320	12,6	60	200
LPGH-32	50	1-31/32	67	2,64	25	375	100	1500	1,80	1,21	400	15,8	60	200



LPGH – Gas Delivery Hose

Standards: EN 1762:2017/D – Type M

Applications: suitable for the delivery of liquefied petroleum gas, LPG and natural gas

Temperature range: -30°C (-22°F) to +70°C (+158°F)

Construction:

Tube: smooth bore, black, extruded rubber

Reinforcement: high strength synthetic cord

Cover: wrapped finish, black, synthetic rubber, weather and ozone resistant. Pin pricked.

Electrical resistance: Type M version - below $1 \times 10^2 \Omega$.

Lay line information: Yellow Band - EN 1762:2017 – I.D. – W.P. bar - Ω - quarter and year of production.

Seagull Fittings Limited

90 Roebuck Lane, West Bromwich, west Midlands B70 6QX

Tel +44(0)121 525 0020 Fax +44(0)121 525 1116 sales@seagullfittings.co.uk